



A dedicated range of products for wine labelling

TECHNICAL DATA SHEET *(provisional)*

Issued:
09.09.2011

Product: **PP Transparent Glossy K6d P6** Code: **7652 K6d P6**

Face Material: **PP Transparent Glossy**
Highly transparent Polypropylene, 60μ, glossy with topcoat.

Thickness: 60 μm (ISO 534)

Adhesive: **P6**

Permanent acrylic adhesive, solvent free, provides very good transparency, excellent resistance to UV-light and ageing.
Complies with EN 71/3 and European packaging directive 94/62/EC (heavy metals).
ISEGA certified for application on dry and moist, non-fatty food.

Adhesion (FTM1 on glass) : > 8 N/25mm
Minimum Application Temperature: > 5°C
Service Temperature: - 25°C to + 75°C

Liner: **K6d**

White supercalandered glassine paper, with good die-cutting and labelling properties.
Solvent free siliconization for highest labelling velocities.

Basis Weight: 65 g/m² (ISO 536) Thickness: 57 μm (ISO 534)

Note: Shelf-life: 24 months when stored at 23°C and 50% RH

WARRANTY:

INTERCOAT materials are manufactured according to highest quality standards and pass stringent quality controls prior to despatch. Any material showing an evident defect of manufacturing will be replaced promptly without charge. The wide range of different applications does not allow to test all possibilities of employment. All statements, technical information and recommendations are based on tests and practical experiences and believed to be reliable but do not constitute a guarantee or warranty. Preliminary tests are recommended for each new application. For any need of advice or technical support the INTERCOAT technical department will be pleased to assist.